

UHD41S 4K HDMI Switcher

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs switches are perfect for any project that requires 24/7 performance.



CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The CE Labs UHD41S is a 4×1 switcher that supports 4K high dynamic range (HDR) formats. It features four HDMI inputs, for receiving video and embedded audio. Supporting 4K/UHD @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI data rates up to 18 Gbps, the UHD41S is the perfect complement to any CE Labs retail HDMI distribution system.

Part of the CE Pro™ Series, the UHD41S includes a number of key features such as advanced HDMI Audio Return Channel (ARC), EDID management, selectable 4K to 1080p downscaling, and HDCP 2.2 support with selectable down-conversion to HDCP 1.4 ensures compatibility with legacy displays.

FEATURES

Support 4K HDR10+ video formats

Patented Cable retention system

Auto-Detect for seamless switching

SPECIFICATIONS MODEL: UHD41S

FEATURES

HDMI 2.0a, HDCP 1.4 & 2.2 and DVI Compliant

Max.video resolutions of 4Kx2K @ 60Hz, 4:4:4

18Gb/S / 600MHz Bandwidth

Compatible with HDR Sources and TVs

Deep Color Compatible on resolutions < 600MHz

Audio extractor supports analog stereo L/R and digital (optical)

Supports ARC extraction to stereo and optical output

4 HDMI inputs one HDMI output switch

Supports RS232 and Remote control

Supports EDID management

Integrated Cable retention bracket (CE labs® patented)

Locking Power Supply

RS232: 115200, 8, N, 1

EDID Management

Patented CE labs patented cable retention system

VIDEO

HDMI 1.4a, 2.0a

HDCP1.4, or 2.2

HDR Support

Color Space: Compliant with BT.601, 709, 2020 (non-const.) RGB Full,

RGB Limited

Resolution: 3840x2160, 60Hz, YCbCr4:4:4 - 8Bit only | 3840x2160, 60Hz,

YCbCr4:2:2 - 8Bit only | 3840x2160, 60Hz, YCbCr4:2:0 - 8, 10, 12Bit | 3840x2160, 30Hz, YCbCr4:4:4 - 8, 10 12Bit | 1920x1080, 60Hz, YCbCr,

4:4:4 - 8, 10, 12Bit | 1280x720, 60Hz, YCbCr, 4:4:4 - 8, 10, 12Bit | RGB Full and RGB Limited are also supported.

HDMI cable 1ft-15ft for 1080P and 4Kx2K 30 / 60(4:2:0)

HDMI cable 1ft-9ft for 3M for 4Kx2K 60 full color

AUDIO

ARC Support

LPCM, Dolby TrueHD, Dolby Digital/plus/EX,DTS,DTS-HD

I/O PORTS

4x HDMI type A Input

1x HDMI type A Output

2.5mm X 5.5mm female locking connector jack

6 pin DIP switch

4 push buttons

1 optical connector

2 3.5mm phone jack

2 LED Green/Red/Yellow

DB9 RS232 connector

POWER SUPPLY

Wall transformaer: 12VDC/1A

Screw on Locking plug 2.5mm x 5.5mm connector

ACCESSORIES

1 Power Adapter 100-240 VAC - 12Vdc 1.0Amp 2.5mm

1 Instruction Manual

1 x IR remote cable

1 x Remote control

MISCELLANEOUS

Dimensions (H) 1", (W) 7.125", (D) 6.75"

Weight 1.4 lbs.

Operating Temp & Humidity 0-55C, 95% Max Rel. Humidity

Integrated Mounting Brackets

Low Profile Design

Rugged (Industrial) Powder Coated Chassis

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States

1-800-767-6189 sales@celabs.com

